

**DESCRIPTION**

Bollard made from injected aluminium with a frosted polycarbonate diffuser protected by an aluminium grille (included). Available in two heights (50cm and 90cm) and in two finishes (light grey or dark grey). G12 70W metal halide light. Electronic components included.

TECHNICAL CHARACTERISTICS

Type:	Beacon
IP Protection degrees:	IP44
IK Protection degrees:	IK08
Units per box:	4
Net Weight (Kg):	4.48
EAN:	8435111076057

Download photometric file .ldt / .ies


**MATERIALS / FINISHES****GEAR**

Gear included: Yes, Magnetic

Luminaire		Measur.		Lamp		
Code	55-9343-34-Z5	Code	55-9342-34-M2	Code	HIT 70/830	
Name	BALIZAS	Name	BALIZAS	Number	1	
Line	Eulumdat	Date	29-04-1994	Position		
Efficiency	31.79%	Coordinate system	CG	Total Flux	5500.00 lm	
Maximum value	354.20 cd	Position	C=0.00 G=70.00	Asymmetrical		
Rectangular Luminaire	Length	170 mm	Width	170 mm	Height	899 mm
Rectangular Luminous Area	Length	123 mm	Width	124 mm	Height	130 mm
Horizontal Luminous Area	0.015252 m2	Emitting area on Plane 180°		0.015990 m2		
Emitting area on Plane 0°	0.015990 m2	Emitting area on Plane 270°		0.016120 m2		
Emitting area on Plane 90°	0.016120 m2	Glare area at 76°		0.019205 m2		
Symmetry Type	Asymmetrical	Maximum Gamma Angle		180		
Measurement Distance	0.00	Measurement Flux		5500.00 lm		
Operator		Source voltage				
Temperature	25.00 °C	Source current				
Humidity	60.00 %	Photocell				
Notes						

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
Eulumdat	HIT 70/830	HIT 70/830 - 70.00 W	5500.00	70.00	1	
C.I.E.	5 28 66 73 32	D DIN 5040		B11		
F UTE	--	B NBN		BZ 10		

170mm x 170mm



C Halfplanes

180.0 — 0.0 (Red line)

270.0 — 90.0 (Blue line)

ULOR 8.49 %

DLOR 23.30 %

RN 26.71 %

