



The photograph may not match the reference exactly. Please read the product description to identify the finish.

Download photometric file .ldt /.ies

TECHNICAL CHARACTERISTICS

Type:	Accessory
Bulb:	36 x LED. Neutral white - 4200K
Power (W):	16
Voltage / Frequency:	100-240V/50-60Hz
Warranty (Years):	2
Units per box:	10
Net Weight (Kg):	0.265
EAN:	8435381404635,00



MATERIALS / FINISHES


GEAR

Multi-voltage electronic gear included (110-240 V / 50-60 Hz)

Luminaire		Measur.		Lamp		
Code	71-9711	Code	71-9711	Code	LED	
Name	LED KIT	Name	LED KIT	Number	1	
Line	IESNA-1995	Date	03-12-2013	Position		
Efficiency	74.24%	Coordinate system	CG	Total Flux	1400.00 lm	
Maximum value	355.84 cd	Position	C=0.00 G=3.00	Asymmetrical		
Rectangular Luminaire	Length	300 mm	Width	300 mm	Height	1 mm
Rectangular Luminous Area	Length	300 mm	Width	300 mm	Height	0 mm
Horizontal Luminous Area	0.090000 m2	Emitting area on Plane 180°		0.000000 m2		
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°		0.000000 m2		
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°		0.021773 m2		
Symmetry Type	Asymmetrical	Maximum Gamma Angle		180		
Measurement Distance	0.00	Measurement Flux		1400.00 lm		
Operator		Source voltage				
Temperature	25.00 °C	Source current				
Humidity	60.00 %	Photocell				
Notes						

Luminaire Lamps					
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
IESNA-1995	LED	71-9711 - 15.10 W	1400.00	15.10	1
C.I.E.	46 76 94 99 74	D DIN 5040		A31	
F UTE	0.74 E + 0.01 T	B NBN		BZ 5	

300mm x 300mm



C Halfplanes

180.0 — 0.0

270.0 — 90.0

ULOR 0.60 %

DLOR 73.64 %

RN 0.81 %

